

NOTES

DIMENSIONS

- ALL DIMENSIONS ARE TO FRAMING UNLESS OTHERWISE STATED.
- BUILDING CONTRACTOR TO CHECK ALL DIMENSIONS BEFORE COMMENCING CONSTRUCTION.
- DOOR/WINDOW OPENING SIZE = H x W. - OFFSET JOINERY IS DIMENSIONED OTHERWISE CONSIDERED CENTRED IN WALL
- ALL SIZES GIVEN FOR WINDOWS AND DOORS ARE ROUGH OPENING SIZES ONLY.

LIGHTING

ILLUMINANCE AT FLOOR LEVEL SHALL BE NO LESS THAN 20 LUX

ALL RECESSED LUMINAIRES TO BE LC. RATED.

INTERNAL DOORS

INTERNAL DOORS TO BE 2.2m HIGH UNLESS STATED OTHERWISE

GLAZING

ALL GLAZING TO COMPLY WITH NZS 4223 INCLUDING SAFETY GLASS TO SHOWER DOORS AND SCREENS

ACCESS

PATIO AND PAVING TO FRONT DOOR TO COMPLY WITH NZBC D1 2.1 SLIP RESISTANCE MAXIMUM STEP HEIGHT TO COMMON/MAIN PRIVATE STAIRWAYS TO BE 190mm.

SMOKE ALARMS - INTERCONNECTED

INTERCONNECTED DOMESTIC SMOKE SP INTERCONNECTED DOWNERS OF ALARM COMPLYING WITH NZBC ACCEPTABLE SOLUTIONS C/AS1 § F7/

HEAT DETECTOR RECOMMENDED TO KITCHEN

KITCHEN SURFACES:

- FOOD PREPARATION AREAS TO HAVE SURFACES ARE TO BE IMPERVIOUS AND EASILY CLEANED.
- WALL LININGS ADJASCENT TO APPLIANCES AND FACILITIES TO HAVE SURFACES THAT CAN BE EASILY MAINTAINED IN A HYGENIC CONDITION

FLOOR FINISH NOTES:

SEALED JOINTS IN ACCORDANCE WITH NZBC E3/AS1
INDICATES CERAMIC TILE FLOORING NOT WATER SPLASH AREAS MUST HAVE A M. 6% WATER ABSORPTION, WATERPROOF GROUTED JOINTS AND LAID OVER A

INDICATES VINYL PLANK FLOORING NOTE:

MEMBRANE IN ACCORDANCE WITH NZBC

WATER SPLASH AREAS MUST HAVE

